



NATIONAL POWER CORPORATION

SUPPLEMENTAL/BID BULLETIN No.1

to the Bid Documents for the:

**Supply and Delivery of One (1) Unit of 10-ton Boom Truck
for Pulangi IV HE Plant
Under P.R. No. MG-PLM24-086**

27 May 2024

All prospective bidders and authorized copyholders of the Bid Documents of the project mentioned above are hereby informed of the changes/clarifications as follows:

REFERENCE SECTION	PREVIOUS VERSION	REVISED VERSION
SECTION III – BID DATA SHEET		
ITB Clause 5.3	For this purpose, similar contracts shall refer to “Supply and Delivery of at least medium-duty trucks (boom truck, light cargo truck, line truck, etc.)	For this purpose, similar contracts shall refer to “Supply and Delivery of at least medium-duty trucks (boom trucks or light cargo crane trucks)”. or light cargo crane trucks”.
SECTION VI – TECHNICAL SPECIFICATIONS		
TS-4.0 Technical Specification TS-4.1 Motor Vehicle	1.1 Truck Specification Vehicle Type Ten (10) wheelers, flatbed with drop sides, tilting cab, 10-ton capacity boom truck, truck mounted crane with straight arm crane, with outrigger/stabilizer, with one (1) spare tire.	Ten (10) wheelers, flatbed with drop sides, tilting cab, 10-ton capacity boom truck, truck mounted crane with straight arm crane, with outrigger/stabilizer, with one (1) spare tire. Size, mm (LXWXH): Manufacturer’s Standard
	Engine Diesel engine with engine displacement not exceeding 8,000cc, turbocharged with intercooler, 4 X 2 drive, at least 260HP @ 2,200RPM rated output with at least 1,020N-m @ 1,400RPM, common rail direct injection type, 25-ton payload capacity.	Diesel engine with engine displacement not exceeding 8,000cc, turbocharged with intercooler, 6 X 4 drive, at least 260HP @ 2,200RPM rated output with at least 1,020N-m @ 1,400RPM, common rail direct injection type, at least 12-ton payload capacity.
PART II – TECHNICAL DATA SHEETS		
B.	1. Vehicle Type Ten (10) wheelers, flatbed with drop sides, tilting cab, 10-ton capacity boom truck, truck mounted crane with straight arm crane, with outrigger/stabilizer, with one (1) spare tire.	Ten (10) wheelers, flatbed with drop sides, tilting cab, 10-ton capacity boom truck, truck mounted crane with straight arm crane, with outrigger/stabilizer, with one (1) spare tire. Size, mm (LXWXH): Manufacturer’s Standard
	2. Engine Diesel engine with engine displacement not exceeding 8,000cc,	Diesel engine with engine displacement not exceeding 8,000cc,



NATIONAL POWER CORPORATION
Gabriel Y. Itchon Building
Senator Miriam P. Defensor Avenue (formerly BIR Road)
Corner Quezon Avenue, Diliman, Quezon City, Philippines
Website: www.napocor.gov.ph



SUPPLEMENTAL/BID BULLETIN NO. 1


Supply and Delivery of One (1) Unit of 10-ton Boom Truck for Pulangi IV HE Plant under PR. No.MG-PLM24-086
27 May 2024

	turbocharged with intercooler, 4 X 2 drive, at least 260HP @ 2,200RPM rated output with at least 1,020N-m @ 1,400RPM, common rail direct injection type, 25-ton payload capacity.	turbocharged with intercooler, 6 X 4 drive, at least 260HP @ 2,200RPM rated output with at least 1,020N-m @ 1,400RPM, common rail direct injection type, at least 12-ton payload capacity.
C. BOOM SPECIFICATION	<ul style="list-style-type: none"> • Maximum Lifting Capacity: 10,000 kg (10-ton) @ 2.5m • Maximum Hook Height: 15.50m • Maximum Working Radius: 13.5m lift kW • Rotation Angle: 360° continuous • Installation Space: 1,200mm • Boom-Type/Sections: Hexagon/4 • Complete with alarms and safety devices for boom safety protection, with boom rest or safety lock when on travel. 	<ul style="list-style-type: none"> • Lifting Capacity: At least 10,000 kg (10-ton) at a working radius of at least 2.5m • Minimum Hook Height: 15.50m • Working Radius: At least 13.5m lift • Rotation Angle: 360° continuous • Installation Space: at least 1,100mm • Boom-Type/Sections: Hexagon/4 • Complete with alarms and safety devices for boom safety protection, with boom rest or safety lock when on travel.
D. TOOLS & DEVICES	Manufacturer's standard toolset – jack, tire wrench, toolbox/pouch, and early warning device including those specified in the Technical Specifications.	Manufacturer's standard toolset – jack, tire wrench, toolbox/pouch, and early warning device including those specified in the Technical Specifications placed in a permanent toolbox.
E. MANUAL AND PARTS CATALOGUE DOCUMENTS	<p>c) Warranty Guide (3 years or 100,000 km whichever comes first).</p> <p>h) Certificate that the passenger bus to be supplied had underwent rustproofing.</p>	<p>c) Warranty Guide</p> <ul style="list-style-type: none"> • for the Truck – At least 2 years or 100,000 km whichever comes first; and • for the Boom – At least 2 years). <p>h) Certificate that the boom truck to be supplied had undergone rustproofing.</p>

All other terms and conditions shall remain the same. Supplemental clarifications shall only supersede the affected requirements.

For the information and guidance of all authorized copyholders of the Bid Documents and prospective bidders.

For the Bids and Awards Committee:


ATTY. MELCHOR P. RIDULME
Senior Vice President, and
Chairman, Bids and Awards Committee